

# LEDPSRT

## FEATURES

Rounded Rectangle rings design with curved corners, this stylish LED Pendant Bar Lamp that generates 3,600 lumens at its full brightness

designed for illuminating dining areas offers a lighting coverage of 15-20sqm



Perfect for:  
over dining tables,  
kitchen bench tops  
as well as bar section  
hanging over workbenches  
or commercial display platform



Input	AC 120-240V 50-60Hz
Output Combined	38W / 40W
Lumen Output Combined	3,600lm at full brightness
LED Chips Type	Dual color LED 2835 diode sets
CT Range	3000 - 5500K
CRI	>80
LED Driver	SAA approval Zigbee protocol integrated LED driver
Material - Lamp frame	Aluminum with Powder Coating Finishing
Material - Diffuser	High-Quality Polycarbonate
Dimension-Diameter	1M / 1.2M
Lifespan	35,000Hrs
IP Rating	IP20 - Indoor use only
Strings / Power Cable Length	1.5m Adjustable
Mounting Method	Ceiling Cap with Expansion Screws are provided

Voice Control Supports Google Home and Amazone Alexa through Nue Bridge or SmartThings Hub

App Control Carry out tasks according to different functions offered by smartphone apps

IFTTT Acts as a terminal device of an IFTTT setup

Wifi Friendly Creates no interfere with the existing Wifi and internet connection

Security It protects your home with home automation tasks during holidays

SAA Approval Comply with SAA Australian Safe Electronic Standard

## SPECIFICATION

Power	Model	Fitting Colour	CRI	Beam Angle	CCT	FLUX	Dimmable
36W	LEDPSRT36W	White	>80	120°	2700K - 6000K	3600lm	Yes
36W	LEDPSRT36W	White	>80	120°	2700K - 6000K	3600lm	Yes




# LEDPSRW45W

## FEATURES

This Run Way shape stylish LED Pendant Bar Lamp generates 4,050 lumens at its full brightness

Designed for illuminating dining areas offers a lighting coverage of 17 - 23sqm



Perfect for:  
over dining tables,  
kitchen bench tops  
as well as bar section  
hanging over workbenches  
or commercial display platform



Input	AC 120-240V 50-60Hz
Output Combined	38W / 40W
Lumen Output Combined	3,600lm at full brightness
LED Chips Type	Dual color LED 2835 diode sets
CT Range	3000 - 5500K
CRI	>80
LED Driver	SAA approval Zigbee protocol integrated LED driver
Material - Lamp frame	Aluminum with Powder Coating Finishing
Material - Diffuser	High-Quality Polycarbonate
Dimension-Diameter	1M / 1.2M
Lifespan	35,000Hrs
IP Rating	IP20 - Indoor use only
Strings / Power Cable Length	1.5m Adjustable
Mounting Method	Ceiling Cap with Expansion Screws are provided

Voice Control Supports Google Home and Amazone Alexa through Nue Bridge or SmartThings Hub

App Control Carry out tasks according to different functions offered by smartphone apps

IFTTT Acts as a terminal device of an IFTTT setup

Wifi Friendly Creates no interfere with the existing Wifi and internet connection

Security It protects your home with home automation tasks during holidays

SAA Approval Comply with SAA Australian Safe Electronic Standard

## SPECIFICATION

Power	Model	Fitting Colour	CRI	Beam Angle	CCT	FLUX	Dimmable
45W	LEDPSRW45W	White	>80	120°	2700K - 6000K	3600lm	Yes



# LEDPSNAK

## FEATURES

A powerful lamp with a combined output of 7500lm at its full brightness.

designed for high ceiling spaces offers a lighting coverage of 25-30sqm



Perfect for:  
over dining tables,  
kitchen bench tops  
as well as bar section  
hanging over workbenches  
or commercial display platform



Input	AC 120-240V 50-60Hz
Output Combined	38W / 40W
Lumen Output Combined	3,600lm at full brightness
LED Chips Type	Dual color LED 2835 diode sets
CT Range	3000 - 5500K
CRI	>80
LED Driver	SAA approval Zigbee protocol integrated LED driver
Material - Lamp frame	Aluminum with Powder Coating Finishing
Material - Diffuser	High-Quality Polycarbonate
Dimension-Diameter	1M / 1.2M
Lifespan	35,000Hrs
IP Rating	IP20 - Indoor use only
Strings / Power Cable Length	1.5m Adjustable
Mounting Method	Ceiling Cap with Expansion Screws are provided

Voice Control Supports Google Home and Amazone Alexa through Nue Bridge or SmartThings Hub

App Control Carry out tasks according to different functions offered by smartphone apps

IFTTT Acts as a terminal device of an IFTTT setup

Wifi Friendly Creates no interfere with the existing Wifi and internet connection

Security It protects your home with home automation tasks during holidays

SAA Approval Comply with SAA Australian Safe Electronic Standard

## SPECIFICATION

Power	Model	Fitting Colour	CRI	Beam Angle	CCT	FLUX	Dimmable
60W	LEDPSNAKS60W	White	>80	120°	2700K - 6000K	4800lm	Yes
100W	LEDPSNAKS100W	White	>80	120°	2700K - 6000K	7500lm	Yes



# LEDPWM


## FEATURES

A powerful lamp with a combined output of 3370lm at its full brightness.

designed for high ceiling spaces offers a lighting coverage of 10-15sqm



Perfect for:  
over dining tables,  
kitchen bench tops  
as well as bar section  
hanging over workbenches  
or commercial display platform



Input	AC 120-240V 50-60Hz
Output	45W
Lumen Output Combined	3300lm at full brightness
LED Chips Type	Dual color LED 5050 diode sets
CT Range	3000-5500K Adjustable through Philips Hue Bridge
CRI	>80
LED Driver	SAA approval Zigbee protocol integrated LED driver
Material - Lamp frame	Aluminum lamp frame with Powder Coating Finishing
Material - Diffuser	High-Quality Polycarbonate
Dimension-Diameter	90 x 25cm
Lifespan	35,000Hrs
IP Rating	IP20 - Indoor use only
Strings / Power Cable Length	1m Adjustable
Mounting Method	Ceiling Cap with Expansion Screws are provided

Voice Control Supports Google Home and Amazon Alexa through Nue Bridge or SmartThings Hub

App Control Carry out tasks according to different functions offered by smartphone apps

IFTTT Acts as a terminal device of an IFTTT setup

Wifi Friendly Creates no interfere with the existing Wifi and internet connection

Security It protects your home with home automation tasks during holidays

SAA Approval Comply with SAA Australian Safe Electronic Standard

## SPECIFICATION

Power	Model	Fitting Colour	CRI	Beam Angle	CCT	FLUX	Dimmable
45W	LEDPWM	White	>80	120°	2700K - 6000K	33700lm	Yes



# LEDPS50W

## FEATURES

Uniquely designed stylish LED Pendant Bar Lamp that generates 4,500 lumens at its full brightness

designed for illuminating dining areas offers a lighting coverage of 17-23sqm



Perfect for:  
over dining tables,  
kitchen bench tops  
as well as bar section  
hanging over workbenches  
or commercial display platform



Input	AC 120-240V 50-60Hz
Output Combined	50W
Lumen Output Combined	4500lm at full brightness
LED Chips Type	Dual color LED 2835 diode sets
CT Range	3000 - 5500K
CRI	>80
LED Driver	SAA approval Zigbee protocol integrated LED driver
Material - Lamp frame	Aluminum with Powder Coating Finishing
Material - Diffuser	High-Quality Polycarbonate
Dimension-Diameter	1.15M
Lifespan	35,000Hrs
IP Rating	IP20 - Indoor use only
Strings / Power Cable Length	1.5m Adjustable
Mounting Method	Ceiling Cap with Expansion Screws are provided

Voice Control Supports Google Home and Amazon Alexa through Nue Bridge or SmartThings Hub

App Control Carry out tasks according to different functions offered by smartphone apps

IFTTT Acts as a terminal device of an IFTTT setup

Wifi Friendly Creates no interfere with the existing Wifi and internet connection

Security It protects your home with home automation tasks during holidays

SAA Approval Comply with SAA Australian Safe Electronic Standard

## SPECIFICATION

Power	Model	Fitting Colour	CRI	Beam Angle	CCT	FLUX	Dimmable
50W	LEDPS50W	White	>80	120°	2700K - 6000K	4500lm	Yes



# LEDP3RSET107W

## FEATURES

A powerful lamp with a combined output of 7500lm at its full brightness.

Designed for high ceiling spaces offers a lighting coverage of 25-30sqm.



Perfect for:  
Hall,  
Living Room,  
Large Dining Areas  
and Above Spiral Staircase

Input	AC 120-240V 50-60Hz
Output Combined	107W (3Rings)
Lumen Output Combined	7500lm at full brightness
LED Chips Type	Dual color LED 5050 diode sets
CT Range	3000-5500K
CRI	>80
LED Driver	SAA approval Zigbee protocol integrated LED driver
Material - Lamp frame	Aluminum with Powder Coating Finishing
Material - Diffuser	High-Quality Polycarbonate
Dimension-Diameter	60cm + 80cm + 100cm
Lifespan	35,000Hrs
IP Rating	IP20 - Indoor use only
Strings / Power Cable Length	1.5m Adjustable
Mounting Method	Ceiling Cap with Expansion Screws are provided

Voice Control Supports Google Home and Amazone Alexa through Nue Bridge or SmartThings Hub

App Control Carry out tasks according to different functions offered by smartphone apps

IFTTT Acts as a terminal device of an IFTTT setup

Wifi Friendly Creates no interfere with the existing WiFi and internet connection

Security It protects your home with home automation tasks during holidays

SAA Approval Comply with SAA Australian Safe Electronic Standard

## SPECIFICATION

Power	Model	Fitting Colour	CRI	Beam Angle	CCT	FLUX	Dimmable
107W	LEDP3RSET107W	White	>80	120°	2700K - 6000K	7500lm	Yes

